

**ArtesianPro Low RPM**

MODEL	HP	TYPE	RPM	VOLTAGE	HZ.	MAX WATTS	WATTS @ MAX. HEAD**	WATTS @ MAX. FLOW**	LIST PRICE
AP 1/4-66	1/4	1Ø TEFC	1725	115/230	50/60	370	230 @ 21 ft.	310 @ 6600 GPH @ 2'	\$905.00
AP 1/3-73	1/3	1Ø TEFC	1725	115/230	50/60	460	240 @ 23 ft.	410 @ 7320 GPH @ 3'	\$967.00
AP 1/2-92	1/2	1Ø TEFC	1725	115/230	50/60	620	330 @ 24 ft.	580 @ 9240 GPH @ 4'	\$1019.00
AP 3/4-105	3/4	1Ø TEFC	1725	115/230	50/60	730	390 @ 23 ft.	710 @ 10,500 GPH @ 5'	\$1,115.50
AP 1-120	1	1Ø TEFC	1725	115/230	50/60	970	480 @ 24 ft.	970 @ 12,000 GPH @ 6'	\$1,171.00

**ArtesianPro High Flow**

MODEL	HP	TYPE	RPM	VOLTAGE	HZ.	MAX WATTS/ AMPS	AMPS @ 230V @ MAX. HEAD**	AMPS @ 230V @ MAX. FLOW**	LIST PRICE
AP 1/2-HF	1/2	1Ø ODP	3450	115/230	60	960 / 4.3	2.6 @ 38 ft.	3.3 @ 8880 GPH @ 3'	\$883.00
AP 3/4-HF	3/4	1Ø ODP	3450	115/230	60	1230 / 5.5	3.4 @ 40 ft.	4.2 @ 10,680 GPH @ 5'	\$925.00
AP 1-HF	1	1Ø ODP	3450	115/230	60	1780 / 7.9	4.1 @ 45 ft.	6.9 @ 13,500 GPH @ 7'	\$1,041.50
AP 1 1/2-HF	1 1/2	1Ø ODP	3450	208-230*	60	2010 / 9.2	5.6 @ 49 ft.	8.0 @ 13,980 GPH @ 8'	\$1,081.50
AP 2-HF	2	1Ø ODP	3450	208-230*	60	2300 / 10.2	5.5 @ 54 ft.	9.2 @ 15,540 GPH @ 10'	\$1,162.00
AP 3-HF	3	1Ø ODP	3450	208-230	60	3100 / 13.4	6.7 @ 58 ft.	13.1 @ 17,820 GPH @ 13'	\$1,252.50
AP 5-HF	5	1Ø ODP	3450	208-230	60	4000 / 17.6	9.5 @ 68 ft.	17.3 @ 19,740 GPH @ 15'	\$1,479.00

**ArtesianPro High Head**

MODEL	HP	TYPE	RPM	VOLTAGE	HZ.	MAX WATTS/AMPS	AMPS @ 230V @ MAX. HEAD**	AMPS @ 230V @ MAX. FLOW**	LIST PRICE
AP 1-HH	1	1Ø ODP	3450	115/230	60	1680 / 7.4	4.6 @ 75 ft.	5.4 @ 9780 GPH @ 4'	\$1,041.50
AP 1 1/2-HH	1 1/2	1Ø ODP	3450	208-230*	60	1960 / 8.6	5.6 @ 79 ft.	6.7 @ 10,980 GPH @ 5'	\$1,081.50
AP 2-HH	2	1Ø ODP	3450	208-230*	60	2300 / 9.9	5.5 @ 81 ft.	7.5 @ 12,480 GPH @ 7'	\$1,162.00
AP 3-HH	3	1Ø ODP	3450	208-230	60	3100 / 13.4	6.8 @ 90 ft.	11.3 @ 13,380 GPH @ 7'	\$1,252.50
AP 5-HH	5	1Ø ODP	3450	208-230	60	4400 / 19.2	11.3 @ 93 ft.	17.6 @ 17,220 GPH @ 12'	\$1,479.00

**Features & Options**

- \* Designed to operate at any point on specified performance curve.
- \* Minimum recommended continuous flow rate of five gallons per minute.
- \* 3 inch suction and discharge ports with quick connect fittings included. 2" or 3" fittings available.
- \* All 1725 RPM motors are enclosed for extra protection and long life.

- \* 316 stainless steel shaft seal.
- \* Optional 16 AWG, 8 ft. cord with 115 volt plug available for 1725 rpm, 1/4HP - 1/2HP.
- \* Optional 12 AWG, 8 ft. cord with 115 volt plug available for 1725 rpm, 3/4HP - 1HP; 3450 rpm, 1hp max.
- \* Saltwater kits available for an additional \$91.00.

- \* A \$6.50 handling & packaging fee applies to each unit.
- \* 3 year limited warranty for fresh water applications.
- \* 1 year limited warranty for salt water applications.

Made with care in the U.S.A.

\* 115V available on special order only and amp draws will be higher.

\*\* Watt and Amp draw ratings are typical, but can vary with different motors and operating voltages.

**PerformancePro Pumps Inc.**